



US005986337A

United States Patent [19]

Takagi et al.

[11] Patent Number: 5,986,337
[45] Date of Patent: Nov. 16, 1999

[54] SEMICONDUCTOR ELEMENT MODULE AND SEMICONDUCTOR DEVICE WHICH PREVENTS SHORT CIRCUITING

63-174344	7/1988	Japan	257/697
1-39051	2/1989	Japan	257/697
1-60542	4/1989	Japan ..	
2-29538	2/1990	Japan ..	
4-146652	5/1992	Japan	
4-199556	7/1992	Japan	257/697
5-102348	4/1993	Japan	257/693
5-144962	6/1993	Japan	257/697

[75] Inventors: Shinichi Takagi; Akinobu Suzuki, both of Tokyo, Japan

[73] Assignee: Mitsubishi Denki Kabushiki Kaisha, Tokyo, Japan

[21] Appl. No.: 09/138,562

[22] Filed: Aug. 24, 1998

[30] Foreign Application Priority Data

Nov. 17, 1997 [JP] Japan 9-315260

[51] Int. Cl.⁵ H01L 23/48

[52] U.S. Cl. 257/693; 257/697; 257/730;

257/692

[58] Field of Search 257/697, 692,
257/693, 698, 730

[56] References Cited

U.S. PATENT DOCUMENTS

4,868,638 9/1989 Hirata et al.

5,398,165 3/1995 Niinou .

5,567,984 10/1996 Zalesinski et al. .

FOREIGN PATENT DOCUMENTS

62-163347 7/1987 Japan 257/697

OTHER PUBLICATIONS

Article issued by Ohm, "Handbook for Electronics and Communication Engineers," *Electric-Communication Hand Book*, dated Mar. 30, 1979, cover pages, and p. 577.

Primary Examiner—Sheila V. Clark

Attorney, Agent, or Firm—Burns, Doane, Swecker & Mathis, LLP

[57]

ABSTRACT

A semiconductor element module includes a package, a semiconductor element arranged on the package, and a plurality of leads provided on sides of the package so that an opening end of each lead is oriented to the side of a package attaching plane, and serving to connect the semiconductor element to an external circuit; wherein a level differences is provided on the side of the package attaching plane of each of package sides so that a space is formed from each the plurality of leads.

10 Claims, 6 Drawing Sheets

